

Q8 T2200

Universal Tractor Transmission Fluid

Description

Q8 T2200 is a multi-purpose product that's been developed for use in off-highway/construction and agricultural equipment having separate engine lubricants. It can also be used as a drive-line lubricant, as an oil-immersed brake/clutch fluid, as a hydraulic fluid and as a transmission lubricant.

Specifications

- API GL-4
- Ford New Holland ESN-M2C 48-C2, 134-D
- John Deere JDM J20C, JDM 3000
- Massey Ferguson CMS M 1135, 1141, 1143, 1145
- GIMA CMS M 1145
- Volvo WB 101, 97302-10, 97303:017
- Case MS 1207, MS 1209, MS 1210
- New Holland NH 410B
- CNH MAT 3505, 3506, 3525
- White New Idea Q-1802, Q-1826
- Caterpillar TO-2
- Allison C-4
- ZF TE-ML 03E, 05F, 06K, 17E
- Komatsu Dresser B06-0002
- Deutz-Allis AC Power Fluid 821 XL
- FNHA-2-C-200.00

Benefits

- Optimal frictional characteristics
- Reduces wet brake noise, thus maintains brake capacity while limiting friction plate wear
- Provides good transmission lubrication
- Protects equipment against rust
- Prevents equipment component corrosion
- Suitable for use as hydraulic fluid
- Contains effective anti-foam agent
- Compatible with conventional elastomers, thus avoiding leakage

Typical Inspection Data

	Method	Units	Inspection Data
Absolute Density, 15 °C	D 1298	kg/m ³	883
Kinematic Viscosity, 40 °C	D 445	mm ² /s	55.1
Kinematic Viscosity, 100 °C	D 445	mm ² /s	9.81
Kinematic Viscosity, 100 °C, after shear test	DIN 51350-6	mm ² /s	7.4
Viscosity Index	D 2270	-	165
Brookfield Viscosity, -10 °C	D 2983	mPa.s	1200
Brookfield Viscosity, -26 °C	D 2983	mPa.s	8000
Flash Point, P-M	D 93	°C	208
Pour Point	D 97	°C	-30
FZG Gear Test, A/8,3/90, Failure Loadstage	DIN 51354/2		11

Health and Safety

Reference should be made to the relevant Q8 Material Safety Data Sheet before use.

Jun 14



Kuwait Petroleum International Lubricants (UK) Ltd

Knowsthorpe Gate, Leeds LS9 0NP. UK

For further assistance contact the Technical help line Telephone +44 (0) 113 2365 223, Fax +44 (0) 870 238 4673

For Customer Sales Contact, Tel +44 (0) 113 2365 204, Fax +44 (0) 113 2485 026. www.Q8Oils.co.uk

In line with our policy of continued improvement, Kuwait Petroleum International Lubricants reserve the right to change specification and availability without prior notice

technical data



Certificate No. FM 89665